

UltraComfort™ Fiber Glass Blowing Insulation

Homeowner Name / Jobsite Name

Homeowner Address / Jobsite Address

ATTIC R-VALUE EVALUATION

ORIGINAL PRODUCT AND NUMBER OF INCHES (If applicable)
ESTIMATED R-VALUE (Please refer to <i>Attic Existing Materials Estimate Table</i> on the right)
R-VALUE ADDED
ESTIMATED TOTAL R-VALUE

ATTIC EXISTING MATERIALS ESTIMATE TABLE*

INSULATION MATERIALS	R-VALUE PER INCH
Fiber Glass Batt	3.14 to 4.30
Fiber Glass Blown	2.20 to 4.30
Rock Wool Batt	3.14 to 4.00
Rock Wool Blown	3.10 to 4.00
Cellulose** Blown	3.13
Vermiculite	2.13

*Source: www.ColoradoEnergy.org

**CertainTeed recommends removing cellulose when upgrading.

ULTRACOMFORT™ ADDED

	R-VALUE	THICKNESS	NET AREA (SQ. FT.)	NUMBER OF BAGS USED
ATTICS				
WALLS				

Installer / Contractor (sign)

Company Name

Date

READ THIS BEFORE YOU BUY

What you should know about R-Values.

The chart shows the R-Value of this insulation. R means resistance to heat flow. The higher the R-Value, the greater the insulating power. Compare insulation R-Values before you buy.

There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel.

To get the marked R-Value, it is essential that this insulation be installed properly.

COVERAGE CHART—OPEN ATTIC APPLICATION

The following thermal performances are achieved at the thicknesses, weights and coverages specified when insulation is installed with pneumatic equipment in a horizontal open blow application.

R-VALUE	MINIMUM BAGS PER 1000 SQ. FT.	MAXIMUM NET SQ. FT. PER BAG COVERAGE	MINIMUM WEIGHT—POUNDS PER SQ. FT.	INITIAL INSTALLED THICKNESS*	MINIMUM SETTLED THICKNESS
To obtain a thermal resistance (R) of:	Bags per 1000 sq. ft. of net area:	Contents of bag shall not cover more than: (sq. ft.)	Weight per sq. ft. of installed insulation shall not be less than: (lbs.)	Installed insulation shall not be less than: (in.)	Minimum settled insulation shall not be less than: (in.)
60	32.1	31.2	0.947	22.75	22.75
49	25.8	38.8	0.761	19.00	19.00
44	23.1	43.4	0.680	17.30	17.30
38	19.8	50.5	0.584	15.20	15.20
30	15.5	64.5	0.457	12.30	12.30
26	13.4	74.7	0.395	10.80	10.80
22	11.3	88.3	0.334	9.30	9.30
19	9.9	101.5	0.291	8.20	8.20
13	6.6	150.5	0.196	5.70	5.70
11	5.7	176.9	0.167	4.90	4.90

R-Values are determined in accordance with ASTM C687 and C518. Complies with ASTM C764 as Type 1 pneumatic application.

*Initial Installed Thickness — TrueComfort® blowing machine and 2-1/2-inch diameter x 100-foot internally corrugated blowing hose. Based upon 29.5 lbs. package net weight.

THERMAL PERFORMANCE—ATTIC BLOWING APPLICATION

- In accordance with the above chart, you must install the minimum number of bags per 1,000 sq. ft. of net area for each R-Value listed.
- The maximum net coverage must not exceed that specified for each R-Value.
- The insulation must be installed at or above the specified installed thickness for each R-Value.
- Failure to install the required minimum weight per sq. ft. of insulation at or above the initial installed thickness will result in reduced R-Value.
- This product should not be mixed with other blown insulations or the thermal claims will become invalid.

DANGER: RECESSED LIGHT FIXTURES—TO PREVENT OVERHEATING, DO NOT INSULATE ON TOP OR WITHIN 3" OF SUCH DEVICES. THIS WARNING DOES NOT APPLY TO TYPE IC LIGHT FIXTURES OR TO FLUORESCENT FIXTURES WITH THERMALLY PROTECTED BALLASTS.

COVERAGE CHART—CLOSED CAVITY RETROFIT (WALLS) APPLICATION

The following thermal performances are achieved at the thicknesses, weights and coverages specified when insulation is installed with pneumatic equipment in sidewalls. Based on a design density of 2.0 pcf.

R-VALUE	REQUIRED OR MINIMUM BAGS PER 1000 SQ. FT.	MAXIMUM NET SQ. FT. PER BAG COVERAGE	MINIMUM WEIGHT—POUNDS PER SQ. FT.	CONSTRUCTION CAVITY TYPE
To obtain a thermal resistance (R) of:	Bags per 1000 sq. ft. of net area:	Contents of bag shall not cover more than: (sq. ft.)	Weight per sq. ft. of installed insulation shall not be less than: (lbs.)	Width by length, (depth)
31	41.0	24.4	1.208	2 x 8 (7.25)
23	31.1	32.2	0.917	2 x 6 (5.50)
15	19.8	50.6	0.583	2 x 4 (3.50)



ASK ABOUT OUR OTHER CERTAINTeED PRODUCTS AND SYSTEMS:

EXTERIOR: ROOFING • SIDING • WINDOWS • FENCE • RAILING • TRIM • DECKING • FOUNDATIONS • PIPE
INTERIOR: INSULATION • GYPSUM • CEILINGS

CertainTeed Corporation
 P.O. Box 860
 Valley Forge, PA 19482

Professional: 800-233-8990
 Consumer: 800-782-8777
www.certainteed.com/insulation

CertainTeed
 SAINT-GOBAIN